

Fuel dispenser

SK 66 Series

Features:

- Customer friendly operation
- Best exterior construction and good appearance
- Trustable highly precise metrology equipment
- High performance for electronic parts
- High quality explosion-proof motor with strong ability against power fluctuation
- Specially designed filtering systems with build-in re-cleanable filter
- With rich functions expansion like POS for smart card and bank card
- Flexible fuel application for gasoline, diesel, and kerosene etc.
- Works well in harsh conditions, like extremely cold, hot, humid, and sand-stormy environment



Beijing Sanki Petroleum Technology Co., Ltd

No 16, 2nd Kechuang Str., Economic-Technological Development Area, Beijing, China, 100023

Tel : +86 10 67892321 Fax: +86 10 67892321

E-mail: business@sankichina.com <http://www.sankichina.com>

Technical specification:

Accuracy for the unit	±0.25%
Flow rate	50L/min
Ambient temperature	-25°C ~ +55°C; or -45°C ~ +55°C
Relative humidity	20% - 95%
Unit noise rate	< 70dB (A);
Inlet vacuum rate for suction pump	≥ 54kPa
Communication	With RS 485 port, or current loop
Power supply	AC 220V(-15%~+10%); (50/60±1)Hz AC 380V(-15%~+10%); (50/60±1)Hz
Digit of sale	0.00~99999.99
Digit of volume	0.00~9999.99
Digit of unit price	0.00~999.99
Totalizer of sale	0~99999999.99
Totalizer of volume	0~9999999.99

Basic Configurations:

- Main board, power board, display board, keypad, control board, pump, motor, flow meter, solenoid valve, electromagnetic counter, filter, nozzle, hose, sight glass

Optional Configuration:

- Stage II Vapor Recovery, card reader payment, double swivel, printer, heater for ultra low temperature, breakaway coupling, emergency shutoff button, shutoff valve for remote dispenser, standard electronics interface to POS and automation fuel management system

Model Range :

Model	Pump unit	Nozzle	Oil	Package Size (mm)	Gross Weight (kg)
SK66ZF222B	suction pump	2	2	1625*755*2310	340
SK66ZF422B		4	2	1625*755*2310	366
SK66ZF632B		6	3	1885*755*2310	395
SK66ZF842B		8	4	2195*755*2310	450
SK66QF222B	Submersible pump	2	2	1625*755*2310	290
SK66QF422B		4	2	1625*755*2310	316
SK66QF632B		6	3	1885*755*2310	330
SK66QF842B		8	4	2195*755*2310	380